

Enterprise 251

General Information

Design: Bethlehem JU-250-MS

Builder: Bethlehem Steel, Beaumont, TX

Year Built: 1978

Class: ABS № A1 Self-Elevating Drilling Unit

Principal Dimensions

Hull Length:166 ftHull Breadth:132 ftDepth:16 ft

Legs: 3 x 312 ft x 12 ft
Leg Spacing: 104 ft – Longitudinal
109 ft – Transverse

Cantilever Envelope: Aft reach 31.5 ft x port/stbd 10 ft

Slot: 48 ft x 50 ft

Operating Parameters

Design Water Depth: 250 ft; 25 ft min.

Max Water Depth: 200 ft (Hurricane)
230 ft (Non-Hurricane)

Drilling Depth Rating: 20,000 ft

Design Criteria: IMO, SOLAS, & MARPOL

Maximum Allowable Loads

Variable Deck Load: 4,500 kips (Includes drilling loads)

 Static Hook Load:
 950,000 lbs.

 Setback:
 500,000 lbs.

 Rotary:
 750,000 lbs.

 Max Cantilever Load:
 950,000 lbs.

Vessel

Storage Capacities

 Fuel:
 1,871 bbls

 Drill Water:
 4,720 bbls

 Potable Water:
 472 bbls

 Liquid Mud:
 1,451 bbls

 Bulk Mud / Cement:
 2,880 ft³ / 3,600 ft³

Sack Material: 2,880 ft / 3,600 ft 3,000 sacks

Power System

Main Power: 4x EMD-12-645-E1

Power System: DC / DC System

Emergency Power: 1x Detroit 16V71

Hoisting Equipment

Cranes: 2x Link Belt 218A with 90 ft boom.

Maximum capacity 35 tons at 20 ft.



Drilling Package

Drilling Equipment

Derrick: Continental Emsco 20RD 147' x 31' x 31'

with a static hook load capacity of 950,000

lbs.

Drawworks: Mid Continent UB-1220-EB 2,000 HP Rotary Table: Continental Emsco T-3750, 37.5".

Top Drive: National – PS 500/500, 500 ton.
Crown Block: Continental Emsco RA60-7, 750 ton
National 500 Series, 500 ton

Traveling Block: National 500 Series, 500 ton

Mud Pumps: 2x Gardner Denver PZ-11 triplex

Shale Shakers: 3x Brandt King Cobra Plus

1x Brandt King Cobra 16/3 Mud

Conditioner

1x Brandt DG-10 Degasser

Well Control System

BOP: 13-5/8" Shaffer annular preventer, 5,000 lb.

WP, H₂S trim.

13-5/8" Cameron Type "U", 10,000 psi WP

double ram preventer, H₂S trim.

13-5/8" Cameron Type "U", 10,000 psi WP

single ram preventer, H₂S trim.

BOP Handling: 2x HercuLink BOP handling overhead

cranes with a rated capacity of 25 tons each, combined capacity of 50 tons.

Additional Data

Accommodations: 58 berths

Helideck: Rated for: Sikorsky S-61